

Material Safety Data Sheet

(In accordance with 2001.58.EC - L212/14)

W64503 - Power Steering Stop Leak

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

IDENTIFICATION OF THE SUBSTANCE OR PREPARATION

W64503 - Power Steering Stop Leak

USE OF THE SUBSTANCE/PREPARATION

Oil additive

COMPANY IDENTIFICATION

COMPANY Wynn's Belgium B.V.B.A.
ADDRESS Industriepark-West 46
9100 SINT-NIKLAAS
TEL +32 (0)3 766.60.20
FAX +32 (0)3 778 16 56
WEBSITE www.wynns.eu
E-MAIL msds@wynns.eu
EMERGENCY TELEPHONE NUMBER
EMERGENCY TELEPHONE NUMBER BIG: +32(0)14/58.45.45

2. HAZARDS IDENTIFICATION

HAZARDS FOR HUMANS AND THE ENVIRONMENT

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

OTHER DANGERS

3. COMPOSITION/INFORMATION ON INGREDIENTS

INFORMATION ON INGREDIENTS

NAME	CAS NO	EINECS/ELINCS	MIN/MAX	SYMBOL	R-PHRASES
2-propanol, 1-(tert-dodecylthio)-; dodecyl hydroxypropyl sulphide	67124-09-8	266-582-5	1 < C < 2,5 %	N	R51/53
Polymethacrylaat	Polymer	Polymer	2,5 < C < 5 %		R53
Solvent naphtha (petroleum), medium aliph.: Straight run kerosine	64742-88-7	265-191-7	0,1 < C < 0,25 %	Xn,N	R10, R38, R51/53, R65
di-isononyl phthalate (DINP)	68515-48-0	271-090-9	5 < C < 10 %		
dodecyl methacrylate	142-90-5	205-570-6	0,1 < C < 0,25 %	XI,N	R36/37/38, R50/53
ethanol, 2,2'-iminobis-, N-tallow-alkyl derivs. strongly refined paraffinic base oil	61791-44-4	263-177-5	0,25 < C < 0,5 % >= 75 %	C,N	R22, R34, R43, R50

4. FIRST AID MEASURES

IN GENERAL

Check the vital functions
Unconscious: maintain adequate airway and respiration
Respiratory arrest: artificial respiration or oxygen
Cardiac arrest: perform resuscitation
Victim conscious with laboured breathing: half-seated
Victim in shock: on his back with legs slightly raised
Vomiting: prevent asphyxia/aspiration pneumonia
Prevent cooling by covering the victim (no warming up)
Keep watching the victim
Give psychological aid
Keep the victim calm, avoid physical strain
Depending on the victim's condition: doctor/hospital

INHALATION

W64503 - Power Steering Stop Leak

	Remove the victim into fresh air
SKIN	Remove clothing before washing wash immediately with plenty of water and soap
EYES	Rinse immediately with plenty of water for 15 minutes Take victim to an ophthalmologist if irritation persists
INGESTION	Rinse mouth with water Do not induce vomiting Consult a doctor/medical service if you feel unwell

5. FIRE-FIGHTING MEASURES

EXTINGUISH. AGENTS-FIRE FIGHTING INSTR.	FIRE EXTINGUISHING MEDIA Polyvalent foam BC powder
	FIREFIGHTING INSTRUCTIONS: Cool tanks/drums with water spray/remove them into safety Solid water jet ineffective as extinguishing medium
FIRE HAZARD	Combustible Heating increases the fire hazard
EXPLOSION HAZARD	No direct explosion hazard
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS	

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION	Gloves Safety glasses Face-shield Protective clothing Heat/fire exposure: compressed air/oxygen apparatus
GENERAL MEASURES	Mark the danger area - No naked flames - Wash contaminated clothes - Exposure to fire/heat: keep upwind - Prevent soil and water pollution - Prevent spreading in sewers
LEAK	Dam up the liquid spill Contain released substance, pump over in suitable containers Plug the leak, cut off the supply
DISPOSAL	Warning! Product may cause floors to be slippery Take up liquid spill into a non combustible material e.g.: sand, earth, vermiculite Scoop absorbed substance into closing containers Clean contaminated surfaces with an excess of water and soap solution Wash clothing and equipment after handling

7. HANDLING AND STORAGE

HANDLING THE PRODUCT	Comply with the legal requirements
----------------------	------------------------------------

W64503 - Power Steering Stop Leak

Observe normal hygiene standards
Clean contaminated clothing
Keep away from naked flames/heat

STORAGE

STORAGE AREA

Meet the legal requirements - Keep out of direct sunlight

CONTAINERS

CONTAINERS : REQUIREMENTS

closing
correctly labelled
meet the legal requirements

SPECIFIC APPLICATIONS

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTION

Gloves
safety glasses or face shield
Protective clothing
Insufficient ventilation: wear respiratory protection

ENVIRONMENTAL PROTECTION EQUIPMENT

MATERIALS FOR PROTECTIVE CLOTHING

nitrile rubber
neoprene

9. PHYSICAL AND CHEMICAL PROPERTIES

GENERAL INFORMATION

STATE OF AGGREGATION

Liquid

ODOUR

oil-like odour

COLOUR

Amber

OTHER PROPERTIES

Clear, Insoluble in water, The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

VALUES OF PHYSICAL PROPERTIES

SPECIFIC GRAVITY	881 kg/m ³ @ 15°C	BOILING POINT	>220°C
VAPOUR PRESSURE	<5 hPa @ 20°C		
VISCOSITY	66.08 mm ² /s @ 40°C // 12.58 mm ² /s @ 100°C		
CLASSIFICATION	DMSO (IP346) <3%		
REFRACTIVE INDEX @ 20°C	1.4764		

HAZARDS FOR EXPLOSION AND FIRE

FLASHPOINT	>150 °C	FIRE HAZARD:	Combustible
AUTO-IGNITION TEMPERATURE	>250 °C		

EXPLOSION RISK

10. STABILITY AND REACTIVITY

STABILITY

Stable under normal conditions

CHEMICAL REACTIONS

On burning: release of e.g. carbon monoxide - carbon dioxide

PROHIBITIONS ON MIXED STORAGE

KEEP SUBSTANCE AWAY FROM:
heat sources
oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS

11. TOXICOLOGICAL INFORMATION

W64503 - Power Steering Stop Leak

VALUES OF CHRONIC TOXICITY

TOXICITY

Literature reports: practically non-toxic if swallowed - Slightly irritant to skin - Slightly irritant to eyes

TOXICITY HAZARD

Slightly irritating

EFFECTS/SYMPTOMS

SYMPTOMS/INJURIES

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: - Skin rash/inflammation

SYMPTOMS/INJURIES AFTER SKIN CONTACT

Slight irritation

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT:

Red skin

Tingling/irritation of the skin

SYMPTOMS/INJURIES AFTER INHALATION

ON HEATING:

Irritation of the nasal mucous membranes

Irritation of the respiratory tract

SYMPTOMS/INJURIES AFTER EYE CONTACT

Irritation of the eye tissue

SYMPTOMS/INJURIES AFTER INGESTION

Abdominal pain

Diarrhoea

Nausea

Vomiting

12. ECOLOGICAL PROPERTIES

MOBILITY

ECOLOGY - GENERAL

Contains environmentally dangerous component(s)

ECOLOGY - WATER

Contains non readily biodegradable component(s)

PERSISTENCE AND DEGRADABILITY

WGK

2

13. DISPOSAL CONSIDERATIONS

Remove to an authorized waste treatment plant

DISPOSAL CODE

Package	
Plastic	15.01.10*
Metal	15.01.11*
Product	
Oil additives	12.01.12*
Fuel additives	14.06.03*
Aqueous solutions	20.01.29*
Airco-cleaner	20.01.19

W64503 - Power Steering Stop Leak

14. TRANSPORT INFORMATION

UN number 3082

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dodecyl hydroxypropyl sulphide), 9 (N), III

ROAD (ADR)

ADR CLASS 9

ADR CLASSIFICATION CODE
ADR SYMBOL

M6



9 - Miscellaneous dangerous substances and articles



N - Environmentally hazardous substance

ADR-PACKING GROUP III

DANGER CODE 90

STATE DURING TRANSPORT (ADR-RID)

Tunnel restriction code (8.6): (E)

SEA (IMDG)

IMDG CLASS 9

MARINE POLLUTANT P

EMS NUMBER

IMDG PACKAGE GROUP

F-A, S-F

III

AIR (IATA/ICAO)

ICAO CLASS 9

ICAO INSTRUCTION PASSENGER
914/Y914

ICAO PACKAGE GROUP III

ICAO INSTRUCTION CARGO 914

15. REGULATORY INFORMATION

Classification and labelling according to the directives 67/548/EEC, 1999/45/EC, 98/8/EC and Regulation (EC) 648/2004.

R-PHRASES

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

S-PHRASES

S61 - Avoid release to the environment. Refer to special instructions/safety data sheets.

ADDITIONAL RISK PHRASES

99.8 - Contains calcium sulfonate, ethanol, 2,2'-iminobis-, N-tallow-alkyl derivs.. May produce an allergic reaction

W64503 - Power Steering Stop Leak

16. OTHER INFORMATION

R-PHRASES

R10 - Flammable
R22 - Harmful if swallowed
R34 - Causes burns
R36/37/38 - Irritating to eyes, respiratory system and skin
R38 - Irritating to skin
R43 - May cause sensitisation by skin contact
R50 - Very toxic to aquatic organisms
R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R53 - May cause long-term adverse effects in the aquatic environment
R65 - Harmful: may cause lung damage if swallowed

REVISION

§§ 3,14

Sources of key data used: Raw material suppliers' data sheets were used as key data sources in the preparation of this safety data sheet.

This safety data sheet has been made in accordance with the directives 91/155/EEG, 93/112/EEG, 2001/58/EG and Reach regulation 1907/2006.

It completes the technical directions for use, but does not replace it.

The data mentioned on these documents are to our knowledge correct on the date of publication and are provided on the assumption that the product will be used as indicated by the manufacturer/supplier. The indication of these safety data, without being considered as complete, helps the user to fulfil his obligations with regard to dangerous substances. The user is obliged to evaluate the product and use it in a safe way in compliance with the effective laws and stipulations. The user has to make sure that all regulations as to human and environmental protection during handling, storage and use of the products are observed.
