

Material Safety Data Sheet

(In accordance with 2001.58.EC - L212/14)

W80179 - Viscotene (Aerosol)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

IDENTIFICATION OF THE SUBSTANCE OR PREPARATION

W80179 - Viscotene (Aerosol)

USE OF THE SUBSTANCE/PREPARATION

Synthetic lubricant.

COMPANY IDENTIFICATION

COMPANY Wynn's Belgium B.V.B.A.
 ADDRESS Industriepark-West 46
 9100 SINT-NIKLAAS
 TEL +32 (0)3 766.60.20
 FAX +32 (0)3 778 16 56
 WEBSITE www.wynns.eu
 E-MAIL msds@wynns.eu
 EMERGENCY TELEPHONE NUMBER
 EMERGENCY TELEPHONE NUMBER BIG: +32(0)14/58.45.45

2. HAZARDS IDENTIFICATION



F+ -
extremely
flammable



Xi - irritant



N -
dangerous
for the
environment

HAZARDS FOR HUMANS AND THE ENVIRONMENT

Extremely flammable - Irritating to skin - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment - Vapours may cause drowsiness and dizziness

OTHER DANGERS

3. COMPOSITION/INFORMATION ON INGREDIENTS

INFORMATION ON INGREDIENTS

| NAME | CAS NO | EI NECS/ELINCS | MIN/MAX | SYMBOL | R-PHRASES |
|---|------------|----------------|------------------|--------|---|
| Alkyl phosphate | | | 1 < C < 2,5 % | Xi | R38, R41 |
| Naphtha (petroleum), hydrotreated light: Low boiling point hydrogen treated naphtha | 64742-49-0 | 265-151-9 | 5 < C < 15 % | F,Xn,N | R11, R38, R51/53, R65, R67 |
| butane | 106-97-8 | 203-448-7 | 15 < C < 25 % | F+ | R12 |
| cyclohexane | 110-82-7 | 203-806-2 | 0,5 < C < 1 % | F,Xn,N | R11, R38, R50/53, R65, R67 |
| heptane [and isomers] | 142-82-5 | 205-563-8 | 2,5 < C < 5 % | F,Xn,N | R11, R38, R50/53, R65, R67 |
| hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6)) | 73513-42-5 | | 0,25 < C < 0,5 % | F,Xn,N | R11, R38, R51/53, R65, R67 |
| methylcyclohexane | 108-87-2 | 203-624-3 | 2,5 < C < 5 % | F,Xn,N | R11, R38, R51/53, R65, R67 |
| n-hexane | 110-54-3 | 203-777-6 | 0,25 < C < 0,5 % | F,Xn,N | R11, R38, R48/20, R51/53, R62, R65, R67 |
| octane [and isomers] | 111-65-9 | 203-892-1 | 5 < C < 15 % | F,Xn,N | R11, R38, R50/53, R65, R67 |
| propane | 74-98-6 | 200-827-9 | 15 < C < 25 % | F+ | R12 |

4. FIRST AID MEASURES

IN GENERAL

Check the vital functions
 Unconscious: maintain adequate airway and respiration
 Respiratory arrest: artificial respiration or oxygen
 Cardiac arrest: perform resuscitation
 Victim conscious with laboured breathing: half-seated

W80179 - Viscotene (Aerosol)

Victim in shock: on his back with legs slightly raised
Vomiting: prevent asphyxia/aspiration pneumonia
Prevent cooling by covering the victim (no warming up)
Keep watching the victim
Give psychological aid
Keep the victim calm, avoid physical strain
Depending on the victim's condition: doctor/hospital

INHALATION

Remove the victim into fresh air
Respiratory problems: consult a doctor/medical service

SKIN

wash immediately with plenty of water and soap
Take victim to a doctor if irritation persists

EYES

Rinse immediately with plenty of water
Take victim to an ophthalmologist if irritation persists

INGESTION

Not applicable

5. FIRE-FIGHTING MEASURES

EXTINGUISH. AGENTS-FIRE FIGHTING INSTR.

FIRE EXTINGUISHING MEDIA

Water spray
AFFF foam

FIREFIGHTING INSTRUCTIONS:

Take account of environmentally hazardous firefighting water
If exposed to fire cool the closed containers by
All extinguishing media allowed
Physical explosion risk: extinguish/cool from behind cover
Solid water jet ineffective as extinguishing medium

FIRE HAZARD

DIRECT FIRE HAZARD

Flammable
Gas/vapour flammable with air within explosion limits

INDIRECT FIRE HAZARD

Fire/heat: explosive hazard bigger than fire hazard

EXPLOSION HAZARD

Aerosol may explode under the effect of heat
Gas/vapour explosive with air within explosion limits
May be ignited by sparks

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION

Gloves
Safety glasses
Protective clothing
Large spills/in enclosed spaces: compressed air apparatus
Heat/fire exposure: compressed air/oxygen apparatus

GENERAL MEASURES

W80179 - Viscotene (Aerosol)

Mark the danger area - Stop engines and no smoking - No naked flames or sparks - Spark- and explosionproof appliances and lighting equipment - Prevent soil and water pollution - Prevent spreading in sewers - Exposure to fire/heat: keep upwind - Exposure to fire/heat: consider evacuation - Exposure to heat: seal off low-lying areas - Exposure to heat: have neighbourhood close doors and windows - Wash contaminated clothes

LEAK

Measure the concentration of the explosive gas-air mixture
NO open flames, NO sparks
Mark the danger area

DISPOSAL

Take up liquid spill into inert absorbent material, e.g.: sand
Scoop absorbed substance into closing containers
Carefully collect the spill/leftovers
Wash clothing and equipment after handling
Clean contaminated surfaces with an excess of water and soap solution

7. HANDLING AND STORAGE

HANDLING THE PRODUCT

Comply with the legal requirements
Carry operations in the open/under local exhaust/ventilation or with respiratory protection
Observe normal hygiene standards
Remove contaminated clothing immediately
Clean contaminated clothing
Use spark-/explosionproof appliances and lighting system
Keep away from naked flames/heat
Keep away from ignition sources/sparks

STORAGE

STORAGE AREA

Store at ambient temperature - Keep out of direct sunlight - Fireproof storeroom - Ventilation at floor level - Provide for a tub to collect spills - Meet the legal requirements

STORAGE TEMPERATURE

< 45°C

CONTAINERS

CONTAINERS : MATERIAL SELECTION aerosol

CONTAINERS : REQUIREMENTS correctly labelled

meet the legal requirements

SPECIFIC APPLICATIONS

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTION

Gloves
Safety glasses
Insufficient ventilation: wear respiratory protection

ENVIRONMENTAL PROTECTION EQUIPMENT

MATERIALS FOR PROTECTIVE CLOTHING

GIVE GOOD RESISTANCE:

nitrile rubber

neoprene

GIVE POOR RESISTANCE:

natural rubber

PVC

W80179 - Viscotene (Aerosol)

9. PHYSICAL AND CHEMICAL PROPERTIES

GENERAL INFORMATION

| | |
|----------------------|--|
| STATE OF AGGREGATION | Liquid Aerosol Liquid, under gas pressure |
| ODOUR | characteristic odour |
| OTHER PROPERTIES | Physical and chemical properties of the active product without gas., Viscous, Insoluble in water, Soluble in naphtha, The physical and chemical data in this section are typical values for this product and are not intended as product specifications. |

VALUES OF PHYSICAL PROPERTIES

SPECIFIC GRAVITY ± 824 kg/m³ @ 15°C

HAZARDS FOR EXPLOSION AND FIRE

EXPLOSION RISK

10. STABILITY AND REACTIVITY

STABILITY

Stable under normal conditions

CHEMICAL REACTIONS

Upon combustion CO and CO₂ are formed

PROHIBITIONS ON MIXED STORAGE

KEEP SUBSTANCE AWAY FROM:

heat sources
ignition sources

HAZARDOUS DECOMPOSITION PRODUCTS

11. TOXICOLOGICAL INFORMATION

VALUES OF CHRONIC TOXICITY

TOXICITY

ACUTE TOXICITY - Harmful: may cause lung damage if swallowed - Irritant to the skin - Moderately irritant for eyes - Slightly irritant to respiratory organs - CHRONIC TOXICITY - Not listed in carcinogenicity class (IARC, EC, TLV, MAK) - Not listed in mutagenicity class (EC, MAK) - Not classified as toxic to reproduction (EC)

TOXICITY HAZARD

DIRECT TOXICITY HAZARD - Literature reports harmful - Irritating - INDIRECT TOXICITY HAZARD - Reactions with toxicity hazards: see Reactivity Hazard

EFFECTS/SYMPTOMS

SYMPTOMS/INJURIES AFTER SKIN CONTACT

Red skin
Dry skin
Tingling/irritation of the skin

SYMPTOMS/INJURIES AFTER INHALATION

Irritation of the respiratory tract
Nausea
Dizziness
Disturbances of consciousness
CNS depression

SYMPTOMS/INJURIES AFTER EYE CONTACT

Redness of the eye tissue
Irritation of the eye tissue

12. ECOLOGICAL PROPERTIES

MOBILITY

ECOLOGY - GENERAL According to literature: environmental hazard

W80179 - Viscotene (Aerosol)

ECOLOGY - WATER

Contains ground water contaminating component(s)
Water pollutant (surface water)
Literature reports: toxic to aquatic organisms
Literature reports may cause long-term adverse effects in the aquatic environment

13. DISPOSAL CONSIDERATIONS

Hazardous waste (91/689/EEC)
Remove to an authorized plant for the destruction, neutralization and elimination of hazardous waste
Use appropriate containment to avoid environmental contamination
PACKAGING/CONTAINER
Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001):
15 01 10*
packaging containing residues of or contaminated by dangerous substances

DISPOSAL CODE

| | |
|-------------------|-----------|
| Package | |
| Plastic | 15.01.10* |
| Metal | 15.01.11* |
| Product | |
| Oil additives | 12.01.12* |
| Fuel additives | 14.06.03* |
| Aqueous solutions | 20.01.29* |
| Airco-cleaner | 20.01.19 |

14. TRANSPORT INFORMATION

UN number 1950

UN 1950 AEROSOLS, 2

ROAD (ADR)

ADR CLASS 2

ADR CLASSIFICATION CODE 5F

STATE DURING TRANSPORT (ADR-RID)

Tunnel restriction code (8.6): (D)

SEA (IMDG)

IMDG CLASS 2.1

EMS NUMBER

F-D, S-U

MARINE POLLUTANT P

AIR (IATA/ICAO)

ICAO CLASS 2.1

ICAO INSTRUCTION CARGO 203

ICAO INSTRUCTION PASSENGER
203/Y203

15. REGULATORY INFORMATION

Classification and labelling according to the directives 67/548/EEC, 1999/45/EC, 98/8/EC and Regulation (EC) 648/2004.

W80179 - Viscotene (Aerosol)

SYMBOL



F+ -
extremely
flammable



Xi - irritant



N -
dangerous
for the
environment

R-PHRASES

R12 - Extremely flammable

R38 - Irritating to skin

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R67 - Vapours may cause drowsiness and dizziness

S-PHRASES

S2 - Keep out of reach of children

S16 - Keep away from sources of ignition - No smoking

S23.8 - Do not breathe vapour/spray

S51 - Use only in well ventilated area

S61 - Avoid release to the environment. Refer to special instructions/safety data sheets.

ADDITIONAL RISK PHRASES

96 - Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use

97 - Do not spray on a naked flame or any incandescent material

300 - Without adequate ventilation formation of explosive mixtures may be possible.

16. OTHER INFORMATION

R-PHRASES

R11 - Highly flammable

R12 - Extremely flammable

R38 - Irritating to skin

R41 - Risk of serious damage to eyes

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R62 - Possible risk of impaired fertility

R65 - Harmful: may cause lung damage if swallowed

R67 - Vapours may cause drowsiness and dizziness

REVISION

§§ 3,9,14

Sources of key data used: Raw material suppliers' data sheets were used as key data sources in the preparation of this safety data sheet.

This safety data sheet has been made in accordance with the directives 91/155/EEG, 93/112/EEG, 2001/58/EG and Reach regulation 1907/2006.

It completes the technical directions for use, but does not replace it.

The data mentioned on these documents are to our knowledge correct on the date of publication and are provided on the assumption that the product will be used as indicated by the manufacturer/supplier. The indication of these safety data, without being considered as complete, helps the user to fulfil his obligations with regard to dangerous substances. The user is obliged to evaluate the product and use it in a safe way in compliance with the effective laws and stipulations. The user has to make sure that all regulations as to human and environmental protection during handling, storage and use of the products are observed.