



## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 First edition: 7/09/2009 Last revision: 5/06/2023 Supersedes version of: 21/12/2022 Version: 6.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Name : Spot Primer Anthracite

Product number : 02.0421.5020
Type of product : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use

Use of the substance or preparation : Fast drying, corrosion-resistant 1K insulation primer for treating the last remaining sanded-

through spots in the primer or clear coat (before spraying the base coat).

#### 1.2.2. Uses advised against

No information available

#### 1.3. Details of the supplier of the safety data sheet

PCS Innotec International NV

Schans 4

BE - 2480 Dessel T.: +32 (0) 14 32 60 01 F.: +32 (0) 14 32 60 12 hse@innotec.eu

Distributor:

Innotec Supplies Ltd.

Unit 25 Glenmore Business Park,

Telford RD

UK - SP2 7GL Salisbury, Wiltshire

T.: +44 (0)1722411744 F.: +44 (0)1722411788 info@innotecworld.com

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

BIG: +32 (0) 14 58 45 45

#### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) no 1272/2008 (CLP)

 Aerosol 1
 H222;H229

 Eye Irrit. 2
 H319

 STOT SE 3
 H336

 Aquatic Chronic 3
 H412

Full text of hazard classes, H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

No information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP) : Danger

Contains : n-Butyl acetate; Acetone; Butan-1-ol; 2-Methoxy-1-methylethyl acetate

GHS02

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P260 - Do not breathe spray.

P273 - Avoid release to the environment.

P280 - Wear protective clothing, protective gloves, face protection, eye protection. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

Extra phrases : Without adequate ventilation formation of explosive mixtures may be possible.

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

3.2. Mixtures				
Name	Product identifier	%	Classification according to Regulation (EC) no 1272/2008 (CLP)	
Acetone	CAS number: 67-64-1 EINECS / ELINCS number: 200-662-2 REACH-no: 01-2119471330- 49	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
n-Butyl acetate	CAS number: 123-86-4 EINECS / ELINCS number: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493- 29	10 – 12,5	Flam. Liq. 3, H226 STOT SE 3, H336	
Propane	CAS number: 74-98-6 EINECS / ELINCS number: 200-827-9 REACH-no: 01-2119486944- 21	5 – 10	Flam. Gas 1A, H220 Press. Gas	
Isobutane (Contains < 0,1% butadiene (203-450-8))	CAS number: 75-28-5 EINECS / ELINCS number: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	5 – 10	Flam. Gas 1A, H220 Press. Gas	
Butane	CAS number: 106-97-8 EINECS / ELINCS number: 203-448-7 REACH-no: 01-2119474691- 32	5 – 10	Flam. Gas 1A, H220 Press. Gas	
Titanium oxide	CAS number: 13463-67-7 EINECS / ELINCS number: 236-675-5 REACH-no: 01-2119489379- 17	2,5 – 5	Carc. 2, H351	

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) no 1272/2008 (CLP)
2-Methoxy-1-methylethyl acetate	CAS number: 108-65-6 EINECS / ELINCS number: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791- 29	2,5 – 5	Flam. Liq. 3, H226 STOT SE 3, H336
Nitrocellulose (nitrogen content < 12,6%)	CAS number: 9004-70-0 EINECS / ELINCS number: /	2,5 – 5	Expl. 1.1, H201
Butan-1-ol	CAS number: 71-36-3 EINECS / ELINCS number: 200-751-6 REACH-no: 01-2119484630- 38	≤ 2,5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
Trizinc bis(orthophosphate)	CAS number: 7779-90-0 EINECS / ELINCS number: 231-944-3 EC Index-No.: 030-011-00-6 REACH-no: 01-2119485044- 40	≤1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General advice : Get medical advice/attention if you feel unwell.

Inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing.

Skin contact : No irritant effect

Eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Ingestion : Drink plenty of water. Go into open air and ventilate suspected area. Call a physician

immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation : May cause drowsiness or dizziness.

Skin contact : Repeated exposure may cause skin dryness or cracking.

Eyes contact : Causes serious eye irritation.

## 4.3. Indication of any immediate medical attention and special treatment needed

No information available

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Water spray. Alcohol resistant foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : May form flammable/explosive vapour-air mixture.

Hazardous decomposition products in case of fire : Toxic gases.

#### 5.3. Advice for firefighters

Firefighting instructions : Prevent fire fighting water from entering the environment. Use water spray or fog for

cooling exposed containers.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing.

6.1.1. For non-emergency personnel

Protective equipment : Refer to protective measures listed in Sections 7 and 8.

Emergency procedures : Evacuate unnecessary personnel.

5/06/2023 (Revision date) EN (English) 3/14

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

This product and its container must be disposed of in a safe way, and as per local

legislation.

Other information : Provide adequate ventilation.

#### 6.4. Reference to other sections

Stable in use and storage conditions as recommended in item 7. Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurised container. Protect from sunlight and do not expose to temperatures exceeding

50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. In use, may form flammable vapour-air mixture.

Precautions for safe handling : Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Provide good ventilation in process area to prevent formation of vapour. Take precautionary measures against static discharge. Eliminate all ignition sources if safe to do

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep in

fireproof place. Smoking is forbidden. Store in a dry place. Keep away from ignition

Technical condition(s) : Store in a well-ventilated place. The floor of the depot should be impermeable and

designed to form a water-tight basin

Special rules on packaging : Store in a closed container. Keep only in original container. Store under dry conditions.

#### 7.3. Specific end use(s)

No information available

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

-Butyl acetate (123-86-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	n-Butyl acetate	
IOEL TWA	241 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	723 mg/m³	
IOEL STEL [ppm]	150 ppm	
Remark	(Ongoing)	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831	
United Kingdom - Occupational Exposure Limi	ts	
Local name	Butyl acetate	
WEL TWA (OEL TWA) [1]	724 mg/m³	
WEL TWA (OEL TWA) [2]	150 ppm	
WEL STEL (OEL STEL)	966 mg/m³	
WEL STEL (OEL STEL) [ppm]	200 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

, ,	Acetone (67-64-1)			
EU - Indicative Occupational Exposure Limit (IOEL)				
Local name	Acetone			
IOEL TWA	1210 mg/m³			
IOEL TWA [ppm]	500 ppm			
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC			
United Kingdom - Occupational Exposure Limits	T			
Local name	Acetone			
WEL TWA (OEL TWA) [1]	1210 mg/m³			
WEL TWA (OEL TWA) [2]	500 ppm			
WEL STEL (OEL STEL)	3620 mg/m³			
WEL STEL (OEL STEL) [ppm]	1500 ppm			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
Butane (106-97-8)				
United Kingdom - Occupational Exposure Limits				
Local name	Butane			
WEL TWA (OEL TWA) [1]	1450 mg/m³			
WEL TWA (OEL TWA) [2]	600 ppm			
WEL STEL (OEL STEL)	1810 mg/m³			
WEL STEL (OEL STEL) [ppm]	750 ppm			
Remark	Carc (Capable of causing cancer and/or heritable genetic damage. See paragraphs 49–51), (only applies if Butane contains more than 0.1% of buta-1,3-diene)			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
Butan-1-ol (71-36-3)				
Butan-1-ol (71-36-3)  EU - Indicative Occupational Exposure Limit (IOEL)				
<u> </u>	n-Butyl alcohol			
EU - Indicative Occupational Exposure Limit (IOEL)	1			
EU - Indicative Occupational Exposure Limit (IOEL) Local name	n-Butyl alcohol			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark	n-Butyl alcohol (Ongoing)			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference	n-Butyl alcohol (Ongoing)			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits	n-Butyl alcohol (Ongoing) SCOEL Recommendations			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name	n-Butyl alcohol (Ongoing) SCOEL Recommendations Butan-1-ol			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL)	n-Butyl alcohol (Ongoing) SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm]	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm] Remark	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm] Remark Regulatory reference	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm] Remark Regulatory reference Titanium oxide (13463-67-7)	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm] Remark Regulatory reference Titanium oxide (13463-67-7) United Kingdom - Occupational Exposure Limits	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)  EH40/2005 (Fourth edition, 2020). HSE			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm] Remark Regulatory reference  Titanium oxide (13463-67-7) United Kingdom - Occupational Exposure Limits Local name	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)  EH40/2005 (Fourth edition, 2020). HSE  Titanium dioxide 4 mg/m³ respirable			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm] Remark Regulatory reference Titanium oxide (13463-67-7) United Kingdom - Occupational Exposure Limits Local name WEL TWA (OEL TWA) [1]	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)  EH40/2005 (Fourth edition, 2020). HSE  Titanium dioxide  4 mg/m³ respirable 10 mg/m³ total inhalable			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm] Remark Regulatory reference  Titanium oxide (13463-67-7) United Kingdom - Occupational Exposure Limits Local name WEL TWA (OEL TWA) [1] Regulatory reference	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)  EH40/2005 (Fourth edition, 2020). HSE  Titanium dioxide  4 mg/m³ respirable 10 mg/m³ total inhalable  EH40/2005 (Fourth edition, 2020). HSE			
EU - Indicative Occupational Exposure Limit (IOEL) Local name Remark Regulatory reference United Kingdom - Occupational Exposure Limits Local name WEL STEL (OEL STEL) WEL STEL (OEL STEL) [ppm] Remark Regulatory reference Titanium oxide (13463-67-7) United Kingdom - Occupational Exposure Limits Local name WEL TWA (OEL TWA) [1] Regulatory reference	n-Butyl alcohol (Ongoing)  SCOEL Recommendations  Butan-1-ol 154 mg/m³ 50 ppm  Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)  EH40/2005 (Fourth edition, 2020). HSE  Titanium dioxide  4 mg/m³ respirable 10 mg/m³ total inhalable  EH40/2005 (Fourth edition, 2020). HSE			

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Methoxy-1-methylethyl acetate (108-65-6)		
IOEL TWA [ppm]	50 ppm	
IOEL STEL	550 mg/m³	
IOEL STEL [ppm]	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	1-Methoxypropyl acetate	
WEL TWA (OEL TWA) [1]	274 mg/m³	
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	548 mg/m³	
WEL STEL (OEL STEL) [ppm]	100 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

#### 8.1.2. Recommended monitoring procedures

No information available

#### 8.1.3. Air contaminants formed

No information available

#### 8.1.4. DNEL and PNEC

No information available

#### 8.1.5. Control banding

No information available

## 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

## Appropriate engineering controls:

Ensure good ventilation of the work station.

## 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Safety glasses. In case of inadequate ventilation wear respiratory protection.

### Personal protective equipment symbol(s):









#### 8.2.2.1. Eye and face protection

#### Eye protection:

Wear security glasses which protect from splashes

## 8.2.2.2. Skin protection

#### Skin protection:

Wear suitable protective clothing

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Hand protection:

Where hand contact with the product may occur, the use of gloves (approved according to the EN374 standard) made from the following materials may provide suitable chemical protection: Butyl rubber. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available. In this case a lower breakthrough time may be acceptable as long as appropriate glove maintenance and replacement regimes are rigorously followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Depending on model and material, glove thickness generally should be greater than 0,35 mm. Suitability and durability of a glove is dependent on usage (= frequency and duration of contact), chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Wear appropriate breathing apparatus if air renewal not sufficient to maintain dust/vapour under TLV. Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust

#### 8.2.2.4. Thermal hazards

No information available

#### 8.2.3. Environmental exposure controls

No information available

#### SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Anthracite.

Appearance : Aerosol.

Odour : characteristic.

Odour threshold : Not available

Melting point/melting range : Not available

Freezing point : Not available

Boiling point/range : Not applicable, since the product is an aerosol.

Flammability : Not available
Explosive limits : 1,2 – 13 vol %
Lower explosion limit : Not available
Upper explosion limit : Not available

Flash point : Not applicable, since the product is an aerosol.

Auto-ignition temperature : Not available
Decomposition temperature : Not available
pH : Not available
Viscosity, kinematic : Not available

Solubility : Water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (Log Kow) : Not available
Vapour pressure : Not available
Vapour pressure at 20 °C : 3500 hPa (20°C)
Density : Not available
Relative density (water = 1) : 0,8 (20°C)
Vapour density : Not available
Particle characteristics : Not applicable

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Explosion limits : 1,2 – 13 vol %

9.2.2. Other safety characteristics

V.O.C. (V.O.S.) : 682,9 g/l

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Extremely flammable aerosol. In use, may form flammable/explosive vapour-air mixture.

#### 10.2. Chemical stability

Stable under normal conditions.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 10.3. Possibility of hazardous reactions

No information available

#### 10.4. Conditions to avoid

No information available

#### 10.5. Incompatible materials

No information available

#### 10.6. Hazardous decomposition products

No information available

SECTION	11. Toyicologia	cal information
SECTION	11: 10X(C0(00)	#1

4	1 1	Informatio	n on hazard o	dagage as a	defined in I	Dogulation	(EC) No	4272/2000
1	1.1	. Intormatio	n on nazaro (	Hasses as (	ietinea in i	Redulation	(FG) NO	12/2/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

LD50/oral/rat	10800 mg/kg
LD50/dermal/rabbit	> 17600 mg/kg
LC50/inhalation/4h/rat	> 21 mg/m³

#### Acetone (67-64-1)

LD50/oral/rat	5800 mg/kg
LD50/dermal/rabbit	> 15800 mg/kg
LC50/inhalation/4h/rat	76 mg/m³

### Trizinc bis(orthophosphate) (7779-90-0)

LD50 dermal rat > 5000 mg/kg

#### Butane (106-97-8)

LC50/inhalation/4h/rat 658000 mg/m³

## Butan-1-ol (71-36-3)

LD50/oral/rat	2292 mg/kg
LD50/dermal/rabbit	3430 mg/kg
LC50/inhalation/4h/rat	17,76 mg/m <sup>3</sup>

### Titanium oxide (13463-67-7)

	LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rabbit		> 10000 mg/kg
	LC50/inhalation/4h/rat	3,43 mg/l
LC50 Inhalation - Rat (Dust/Mist)		> 6,82 mg/l/4h

## 2-Methoxy-1-methylethyl acetate (108-65-6)

LD50/oral/rat	8530 mg/kg
LD50/dermal/rabbit	> 5000 mg/kg
LC50/inhalation/4h/rat	> 10000 mg/m³

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

#### n-Butyl acetate (123-86-4)

STOT-single exposure May cause drowsiness or dizziness.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Butan-1-ol (71-36-3)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
2-Methoxy-1-methylethyl acetate (108-65-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

#### 11.2. Information on other hazards

No information available

## SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Hazardous to the aquatic environment, long–te (chronic)	rm : Harmful to aquatic life with long lasting effects.
n-Butyl acetate (123-86-4)	
LC50/96h/fish	18 mg/l (Pimephales promelas)
LC50 - Other aquatic organisms [1]	205 mg/l (24h, Daphnia magna)
EC50/48h/daphnia magna	44 mg/l
EC50 - Other aquatic organisms [1]	320 mg/l (96h, Algae)
Acetone (67-64-1)	
LC50/96h/fish	8300 mg/l
LC50 - Other aquatic organisms [1]	2262 mg/l (48h, Daphnia magna)
EC50 - Other aquatic organisms [1]	8450 mg/l (48h, crustacean (water flea))
EC50 96h - Algae [1]	7200 mg/l
Trizinc bis(orthophosphate) (7779-90-0)	
LC50/96h/fish	0,14 mg/l
EC50/48h/daphnia magna	0,04 mg/l
EC50 - Other aquatic organisms [1]	0,136 mg/l (72h, Algae)
Butan-1-ol (71-36-3)	
LC50/96h/fish	1376 mg/l (Pimephales promelas)
EC50/48h/daphnia magna	1328 mg/l
EC50 - Other aquatic organisms [2]	8500 mg/l (72h, Algae)
Titanium oxide (13463-67-7)	
LC50/96h/fish	> 1000 mg/l
LC50 - Fish [2]	> 10000 mg/l
EC50/24h/daphnia magna	2 mg/l
EC50 - Other aquatic organisms [1]	> 10000 mg/l
EC50 - Other aquatic organisms [2]	61 mg/l
NOEC (chronic)	0,01 mg/l rat
NOEC chronic algae	56000 mg/l
2-Methoxy-1-methylethyl acetate (108-65	i-6)
LC50/96h/fish	100 – 180 (oncorhynchus mykiss)
EC50 - Other aquatic organisms [2]	> 500 mg/l Daphnia magna

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 12.2. Persistence and degradability

No information available

#### 12.3. Bioaccumulative potential

No information available

#### 12.4. Mobility in soil

No information available

## 12.5. Results of PBT and vPvB assessment

No information available

## 12.6. Endocrine disrupting properties

No information available

#### 12.7. Other adverse effects

Other adverse effects : Harmful to fishes.

Additional information : Harmful to aquatic organisms. Danger to drinking water, even if small amounts leak into the

subsoil. Avoid release to the environment.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste / unused products : Should not be landfilled with household waste. Avoid release to the environment.

European List of Waste (LoW) code : 08 01 11\* - waste paint and varnish containing organic solvents or other dangerous

substances

15 01 04 - metallic packaging

#### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

#### 14.1. UN number or ID number

UN-No. (ADR) : UN 1950 UN-No. (IMDG) : UN 1950 UN-No. (IATA) : UN 1950

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS, flammable

Proper Shipping Name (IMDG) : AEROSOLS

Proper Shipping Name (IATA) : Aerosols, flammable

Transport document description (ADR) : UN 1950 AEROSOLS, flammable, 2.1, (D)

Transport document description (IMDG) : UN 1950 AEROSOLS, 2

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1

### 14.3. Transport hazard class(es)

**ADR** 

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1



#### **IMDG**

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



#### IATA

Transport hazard class(es) (IATA) : 2.1

Danger labels (IATA) : 2.1

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Further information : No supplementary information available

#### 14.6. Special precautions for user

**Overland transport** 

Classification code (ADR) : 5F
Limited quantities (ADR) : 1I
Transport category (ADR) : 2
Tunnel restriction code : D

Transport by sea

Limited quantities (IMDG) : 1 L
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U

#### Air transport

No data available

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU Regulations

#### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

## PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### VOC Directive (2004/42)

V.O.C. (V.O.S.) : 682,9 g/l

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 15.1.2. National regulations

No information available

## 15.2. Chemical safety assessment

No information available

<b>SECTION 16:</b>	SECTION 16: Other information			
Indication of ch	Indication of changes			
Section	Changed item	Change	Comments	
	Last revision			
	Supersedes			
2.3				
8.1				
8.2				
9.1				
9.2				
11.2.				
12.6				
12.7				
15				
16				

Abbreviations and acronyms:	
	ACGIH = American Conference of Governmental Industrial Hygienists
	ADR = Accord européen sur le transport des marchandises dangereuses par Route
	ATE = Acute Toxicity Estimate
	CAS = Chemical Abstracts Service
	CLP = Classification, labelling and packaging
	CSR = Chemical Safety Report
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No-Effect Level
	DPD = Dangerous Preparation Directive
	DSD = Dangerous Substance Directive
	EINECS/ELINCS = European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	HTP = Haitallisiksi tunnetut pitoisuudet
	IATA = International Air Transport Association
	ICAO = International Civil Aviation Organization
	IMDG = International Maritime Code for Dangerous Goods
	IOELV = Indicative Occupational Exposure Limit Value (EU)
	LC50 = Lethal concentration, 50 percent
	LD50 = Lethal dose, 50 percent
	LEL = Lower Explosion Limit
	MAK = Maximale Arbeitsplatzkonzentrationen
	MAL-kode = Måleteknisk Arbejdshygiejnisk Luftbehov
	NDS = Najwyższe Dopuszczalne Stężenie

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
	N.O.S. = Not Otherwise Specified
	NDSCh = Najwyższe Dopuszczalne Stężenie Chwilowe
	OEL = Occupational Exposure Limits
	PBT = Persistent, bioaccumulative and toxic
	PNEC = Predicted No-Effect Concentration
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	RID = Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail).
	STEL = Short term exposure limit
	STOT RE = specific target organ toxicity repeated exposure
	STOT SE = specific target organ toxicity single exposure
	SVHC = Substance of Very High Concern
	TLV = Threshold Limit Value
	TRGS = Technischen Regeln für Gefahrstoffe
	TWA = time weighted average
	UEL = Upper Explosion Limit
	VLA-EC = valores límite ambientales para la exposición de corta duración
	VLA-ED = valores límite ambientales para la exposición diaria
	VLE = Valeur Limite d'exposition
	VME = Valeur Limite de Moyenne d'exposition
	VOC = Volatile Organic Compounds
	vPvB = very Persistent and very Bioaccumulative
	WGK = Wassergefärhdungsklasse

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Expl. 1.1	Explosives, Division 1.1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H201	Explosive; mass explosion hazard.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Disclaimer with regard to REACH:

The information provided in this Safety Data Sheet is consistent with the information in the Chemical Safety Report, as far as this information was available at the time of compilation (see last revision date).

#### Disclaimer:

The information of this Safety Data Sheet is based on the present state of our knowledge and on current EC and national laws, as the users' working conditions are beyond our knowledge and control. The user is always responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this Safety Data Sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information provided relates only to the specific product designated and may not be valid for such product used in combination with any other product. The product must not be used for any purposes other than those specified without first obtaining written handling instructions.