



Professional Products



Workshop & Service Products

Super Glue with activator

Description

Industrial Strength Super Glue with Activator.

Properties

- Low/medium viscosity Super Glue
- Activator can be used to speed cure time & help bond difficult substrates

Applications

- Ideal for bonding a wide variety of materials around the car, workshop & home.
- Will bond, most plastics, rubber, metal, wood, glass.



Directions

1. Ensure surfaces to be bonded are clean & dry.
 2. Apply Super Glue sparingly to one surface only.
 3. Press parts together until the glue has cured.
- For instant bonding or for difficult to bond materials, use Wynn's activator.
 1. Follow instructions 1-2 above.
 2. Apply activator sparingly to the other surface.
 3. Press parts together until glue has cured.
 - Alternatively apply glue to one surface, press together and spray the activator onto the join.

Technical Data

Appearance:	Clear almost colourless liquid
Odour:	Sharp, Pungent
PH:	6-7

Packaging

Product number:	B90088
Content:	20g/50 ml
Box:	6 x 20g/50 ml
Languages on label:	EN

Wynn Oil UK – Unit 4 Parbrook Close, Coventry, West Midlands, CV4 9XY
Telephone: **02476 472634** – E-mail: sales@wynns.uk.com

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.