



Silicone-Lube (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

MSDS Version: E04.00

Date of issue: 03/04/2015

Blend Version: 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Silicone-Lube (Aerosol)
Product code : WOUK W10479

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Cleaning product

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn Oil U.K. (ITW Additives UK)
Unit 4, Parbrook Close, Coventry
CV4 9XY West Midlands - UK
T 02476 472634
helpline@wynns.uk.com - <http://www.wynns.uk.com>

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1	H222;H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F+; R12
Xi; R38
N; R51/53
R67

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

:



GHS02



GHS07



GHS09

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP)

: P261 - Avoid breathing vapours, spray
P280 - Wear protective gloves
P271 - Use only outdoors or in a well-ventilated area
P102 - Keep out of reach of children

Silicone-Lube (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% w	Classification according to Directive 67/548/EEC
hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	(EC no) 926-605-8 (REACH-no) 01-2119486291-36	30 - 50	F; R11 Xi; R38 N; R51/53 Xn; R65 R67

Propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	10 - 30	F+; R12
Butane n-	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0 (REACH-no) 01-2119474691-32	10 - 30	F+; R12
isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	1 - 10	F+; R12

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	(EC no) 926-605-8 (REACH-no) 01-2119486291-36	30 - 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	10 - 30	Flam. Gas 1, H220
Butane n-	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0 (REACH-no) 01-2119474691-32	10 - 30	Flam. Gas 1, H220
isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	1 - 10	Flam. Gas 1, H220

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Check the vital functions. Victim conscious with laboured breathing: half-seated. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Silicone-Lube (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. As it is a spray can packaging it is most unlikely that large quantities will be swallowed.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Vapours may cause drowsiness and dizziness.
Symptoms/injuries after inhalation	: Nausea. May cause respiratory irritation. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/injuries after skin contact	: Dry skin. Red skin. skin corrosion/irritation.
Symptoms/injuries after eye contact	: May cause slight irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. AFFF foam. ABC-powder.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol. Heating may cause a fire or explosion. Gas/vapour spreads at floor level: ignition hazard. Gas/vapour flammable with air within explosion limits.
Explosion hazard	: Gas/vapour explosive with air within explosion limits. May be ignited by sparks. Explosion risk in case of fire.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Physical explosion risk: extinguish/cool from behind cover.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves. Protective goggles. Large spills/in enclosed spaces: compressed air apparatus.
Emergency procedures	: Mark the danger area. No naked flames, sparks, and do not smoke. Stop engines and no smoking. Close doors and windows of adjacent premises. Seal off low-lying areas. Exposure to fire/heat: keep upwind. Use spark-/explosionproof appliances and lighting system. Wash contaminated clothes.

6.1.2. For emergency responders

Emergency procedures	: Ventilate area.
----------------------	-------------------

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Scoop absorbed substance into closing containers. Wash clothing and equipment after handling.
-------------------------	---

6.4. Reference to other sections

No additional information available

Silicone-Lube (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Keep away from naked flames/heat. Keep away from sources of ignition - No smoking. Use spark-/explosionproof appliances and lighting system. Meet the legal requirements.
- Hygiene measures : Observe normal hygiene standards. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- Storage temperature : < 45 °C
- Heat and ignition sources : Keep away from sources of ignition - No smoking.
- Prohibitions on mixed storage : Keep away from strong acids and strong oxidizers.
- Storage area : Protect from heat and direct sunlight. Store in a dry place. Store in a well-ventilated place. Ventilation along the floor. Meet the legal requirements.
- Special rules on packaging : meet the legal requirements. correctly labelled.
- Packaging materials : Pressurised small gas containers (aerosol cans).

7.3. Specific end use(s)

See product bulletin for detailed information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Butane n- (106-97-8)

Belgium Limit value (ppm) 1000 ppm

Propane (74-98-6)

Belgium Limit value (ppm) 1000 ppm

isobutane (75-28-5)

Belgium Limit value (ppm) 1000 ppm

8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures.
- Personal protective equipment : Gloves. Protective goggles.



- Hand protection : Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.
- Other information : Breakthrough time : >30 min. Thickness of the glove material >0.1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Aerosol.
- Colour : Colourless.
- Odour : characteristic.
- Odour threshold : No data available
- pH :
- Relative evaporation rate (butylacetate=1) : No data available
- refraction index :
- Melting point : No data available
- Freezing point : No data available

Silicone-Lube (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Boiling point	: < 0 °C
Flash point	: < 0 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: No data available
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

Additional information : The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

LD50 oral rat > 5000 mg/kg

LD50 dermal rabbit > 2000 mg/kg

LC50 inhalation rat (mg/l) > 20 mg/l

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Silicone-Lube (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available. This product contains hazardous components for the aquatic environment.

Ecology - water : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Container under pressure. Do not drill or burn even after use. Remove to an authorized waste treatment plant.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS

Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

Class (ADR) : 2

Subsidiary risk (IMDG) : 2.1

Subsidiary risk (IATA) : 2.1

Danger labels (ADR) : 2.1



14.4. Packing group

Not applicable

14.5. Environmental hazards

Dangerous for the environment :



Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Silicone-Lube (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Transport category (ADR) : 2
Tunnel restriction code (ADR) : D
Limited quantities (ADR) : 1I

14.6.2. Transport by sea

EmS-No. (1) : F-D, S-U

14.6.3. Air transport

Instruction "cargo" (ICAO) : 203
Instruction "passenger" (ICAO) : 203/Y203

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions
Silicone-Lube (Aerosol) is not on the REACH Candidate List
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

Water hazard class (WGK) : 2 - hazard to waters

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
R11	Highly flammable
R12	Extremely flammable
R38	Irritating to skin
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
F+	Extremely flammable
N	Dangerous for the environment
Xi	Irritant

Silicone-Lube (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Xn	Harmful
----	---------

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product