



Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 28/09/2022 Revision date: 24/06/2021 Version: 5.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Xtreme Diesel System Clean
Product code : W12264
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Diesel fuel additive
Function or use category : Fuel additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ITW ADDITIVES INTL B.V.
Industriepark-West 46
9100 Sint-Niklaas
Belgium
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.com

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14 58 45 45 (NL FR EN DE)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)	: Danger
Contains	: C8-C26 branched and linear hydrocarbons – Distillates
Hazard statements (CLP)	: H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P405 - Store locked up.

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P280 - Wear eye protection, protective gloves.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 - Do NOT induce vomiting.
P273 - Avoid release to the environment.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
2-ethylhexan-1-ol (104-76-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
C8-C26 branched and linear hydrocarbons – Distillates	CAS-No.: 848301-67-7 EC-No.: 481-740-5 REACH-no: 01-0000020119-75	≥ 50	Asp. Tox. 1, H304 EUH066
2-butoxyethanol substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108-36	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
2-Ethylhexyl nitrate	CAS-No.: 27247-96-7 EC-No.: 248-363-6 REACH-no: 01-2119539586-27	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 2, H411 EUH044, EUH066
2-ethylhexan-1-ol substance with a Community workplace exposure limit	CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289-20	5 – 10	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, rinse mouth. Do NOT induce vomiting. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after ingestion	: Headache. Abdominal pain. Risk of aspiration pneumonia. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. AFFF foam. ABC-powder.
------------------------------	---------------------------------------

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid. Take precautionary measures against static discharge.
Explosion hazard	: Product is not explosive.

5.3. Advice for firefighters

Firefighting instructions	: Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No open flames. No smoking. Use special care to avoid static electric charges. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable gloves and eye/face protection. protective clothing.
Emergency procedures	: Mark the danger area. Prevent flow to low areas. In confined space use self-contained breathing apparatus. Take off contaminated clothing.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
----------------------	--

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Contain leaking substance, pump over in suitable containers.
Methods for cleaning up	: Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Meet the legal requirements. Repeated exposure may cause skin dryness or cracking. Presents no particular risk when handled in accordance with good occupational hygiene practice.
- Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Gently wash with plenty of soap and water. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Does not require any specific or particular technical measures.
- Storage conditions : Meet the legal requirements. Protect from sunlight. Store in a well-ventilated place. Store in a closed container.
- Storage temperature : < 45 °C
- Storage area : Meet the legal requirements. Ventilation along the floor.
- Special rules on packaging : Meet the legal requirements. Labelling according to.

7.3. Specific end use(s)

Read label before use. Observe the label precautions. See product bulletin for detailed information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-butoxyethanol (111-76-2)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	2-Butoxyethanol
IOEL TWA	98 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	246 mg/m ³
IOEL STEL [ppm]	50 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

Belgium - Occupational Exposure Limits

Local name	2-Butoxyéthanol # 2-Butoxy-ethanol
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002

France - Occupational Exposure Limits

VME (OEL TWA)	49 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	246 mg/m ³
VLE (OEL C/STEL) [ppm]	50 ppm

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethanol (111-76-2)	
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	98 mg/m ³
CK (OEL STEL)	246 mg/m ³
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	100 mg/m ³
TGG-8u (OEL TWA) [ppm]	20 ppm
TGG-15min (OEL STEL)	246 mg/m ³
TGG-15min (OEL STEL) [ppm]	50 ppm
2-ethylhexan-1-ol (104-76-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5,4 mg/m ³
IOEL TWA [ppm]	1 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	110 mg/m ³
AGW (OEL TWA) [2]	20 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)	
PNEC (Sediment)	
PNEC sediment (freshwater)	2,06 mg/kg dwt
PNEC (Soil)	
PNEC soil	1,68 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
2-butoxyethanol (111-76-2)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	89 mg/kg bodyweight/day
Acute - systemic effects, inhalation	1091 mg/m ³
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	98 mg/m ³
Long-term - local effects, inhalation	246 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	89 mg/kg bodyweight
Acute - systemic effects, inhalation	426 mg/m ³
Acute - systemic effects, oral	26,7 mg/kg bodyweight
Long-term - systemic effects, oral	6,3 mg/kg bodyweight/day

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethanol (111-76-2)	
Long-term - systemic effects, inhalation	59 mg/m³
Long-term - systemic effects, dermal	75 mg/kg bodyweight/day
Long-term - local effects, inhalation	147 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	8,8 mg/l
PNEC aqua (marine water)	0,88 mg/l
PNEC aqua (intermittent, freshwater)	9,1 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	34,6 mg/kg dwt
PNEC sediment (marine water)	3,46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2,33 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	463 mg/l
2-Ethylhexyl nitrate (27247-96-7)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,35 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects, dermal	0,52 mg/kg bodyweight/day
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
2-ethylhexan-1-ol (104-76-7)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	53,2 mg/m³
Long-term - systemic effects, dermal	23 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	12,8 mg/m³
Long-term - local effects, inhalation	53,2 mg/m³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	26,6 mg/m³
Long-term - systemic effects, oral	1,1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,3 mg/m³
Long-term - systemic effects, dermal	11,4 mg/kg bodyweight/day
Long-term - local effects, inhalation	26,6 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0,017 mg/l
PNEC aqua (marine water)	0,0017 mg/l
PNEC aqua (intermittent, freshwater)	0,17 mg/l

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethylhexan-1-ol (104-76-7)

PNEC (Sediment)

PNEC sediment (freshwater)	0,284 mg/kg dwt
PNEC sediment (marine water)	0,0284 mg/kg dwt

PNEC (Soil)

PNEC soil	0,047 mg/kg dwt
-----------	-----------------

PNEC (STP)

PNEC sewage treatment plant	10 mg/l
-----------------------------	---------

Hydrocarbons, C10, aromatics, <1% naphthalene

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	151 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	7,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	32 mg/m ³
Long-term - systemic effects, dermal	7,5 mg/kg bodyweight/day

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Does not require any specific or particular technical measures. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

No additional information available

8.2.2.2. Skin protection

Hand protection:

Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer

8.2.2.3. Respiratory protection

No additional information available

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Appearance	: clear.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 64 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 2,5 mm ² /s @40°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 805 kg/m ³ @20°C
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Additional information : The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. On burning: release of harmful/irritant gases/vapours. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)

LD50 oral rat	> 5000 mg/kg bodyweight Sprague-Dawley
LD50 dermal rat	> 2000 mg/kg bodyweight Sprague-Dawley

2-butoxyethanol (111-76-2)

LD50 oral rat	1200 mg/kg bodyweight Rat
LD50 dermal rat	> 2000 mg/kg bodyweight Sprague-Dawley
LD50 dermal rabbit	24h 435 mg/kg New Zealand White

2-Ethylhexyl nitrate (27247-96-7)

LD50 oral rat	> 9600 mg/kg bodyweight Sprague-Dawley
---------------	--

2-ethylhexan-1-ol (104-76-7)

LD50 oral rat	2047 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 Inhalation - Rat	1,1 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

2-ethylhexan-1-ol (104-76-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified
Aspiration hazard : May be fatal if swallowed and enters airways.

Xtreme Diesel System Clean

Viscosity, kinematic	2,5 mm²/s @40°C
----------------------	-----------------

C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)

Viscosity, kinematic	2 – 4,5 mm²/s
----------------------	---------------

2-butoxyethanol (111-76-2)

Viscosity, kinematic	< 3,7 mm²/s
----------------------	-------------

2-Ethylhexyl nitrate (27247-96-7)

Viscosity, kinematic	1,767 mm²/s
----------------------	-------------

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: This product contains hazardous components for the aquatic environment.
Ecology - water	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)

LC50 - Fish [1]	> 1000 mg/l @96h Pimephales promelas
EC50 - Crustacea [1]	> 1000 mg/l @48h Daphnia magna
EC50 - Other aquatic organisms [1]	> 1000 mg/l @72h Pseudokirchneriella subcapitata
NOEC (acute)	> 1000 mg/l @48h Daphnia magna

2-butoxyethanol (111-76-2)

LC50 - Fish [1]	96h 1464 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	48h 1800 mg/l Daphnia magna
EC50 - Other aquatic organisms [1]	72h 911 mg/l Pseudokirchneriella subcapitata
NOEC (acute)	72h 88 mg/l Pseudokirchneriella subcapitata

2-Ethylhexyl nitrate (27247-96-7)

LC50 - Fish [1]	96h 2 mg/l Brachydanio rerio
EC50 - Crustacea [1]	> 12,6 mg/l @48h Daphnia magna
EC50 - Other aquatic organisms [1]	72h 1,57 mg/l Pseudokirchnerella subcapitata

2-ethylhexan-1-ol (104-76-7)

LC50 - Fish [1]	96h 28,2 mg/l pimephales promelas
EC50 - Crustacea [1]	48h 39 mg/l daphnia magna
EC50 - Other aquatic organisms [1]	72h 11,5 mg/l algae (desmodesmus subspicatus)

12.2. Persistence and degradability

C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

2-butoxyethanol (111-76-2)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

2-Ethylhexyl nitrate (27247-96-7)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

2-ethylhexan-1-ol (104-76-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential

C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)

Partition coefficient n-octanol/water (Log Pow)	> 6,5 @40°C
---	-------------

2-butoxyethanol (111-76-2)

Bioaccumulative potential	Slightly bioaccumulative.
---------------------------	---------------------------

2-ethylhexan-1-ol (104-76-7)

Bioaccumulative potential	No bioaccumulation.
---------------------------	---------------------

12.4. Mobility in soil

2-butoxyethanol (111-76-2)

Ecology - soil	Small adsorption.
----------------	-------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.
European List of Waste (LoW) code	: 14 06 03* - other solvents and solvent mixtures 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no REACH substances with Annex XVII restrictions

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class III-1
Store unit : 50 liter
Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.

Xtreme Diesel System Clean

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.