



Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 28.08.2023 Revision date: 08.05.2023 Version: 4.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Petrol Pre Emission Test Treatment
Product code : W35792
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Petrol additive.
Function or use category : Fuel additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

ITW ADDITIVES INTL B.V.
Industriepark-West 46
9100 Sint-Niklaas
BELGIUM
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.com

Distributor

Krafft S.L.U.
Carretera de Urnieta, s/n
20140 Andoain - Guipúzcoa
ESPAÑA
T +34 943 410 400 - F +34 943 410 440

Distributor

Wynn's Automotive France S.A.S.
2 Av. Léonard de Vinci Z.A. Europarc
33600 PESSAC Cedex
FRANCE
T +33 5 57 26 29 00

Distributor

ITW Automotive Aftermarket
Saxon House, 2-4 Victoria Street
SL4 1EN Windsor
UNITED KINGDOM
T +44 (0)24 7647 2634
<http://www.wynns.uk.com>

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14 58 45 45 (NL FR EN DE)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

| | |
|--|------|
| Flammable liquids, Category 3 | H226 |
| Acute toxicity (inhalation:vapour) Category 4 | H332 |
| Skin corrosion/irritation, Category 2 | H315 |
| Serious eye damage/eye irritation, Category 2 | H319 |
| Germ cell mutagenicity, Category 2 | H341 |
| Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation | H335 |
| Specific target organ toxicity – Repeated exposure, Category 2 | H373 |
| Aspiration hazard, Category 1 | H304 |

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

: Danger
: C8-C26 branched and linear hydrocarbons – Distillates; 2-ethylhexan-1-ol; 2-butoxyethanol; reaction mass of ethylbenzene and xylene ; Di-tert-butyl peroxide
: H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H341 - Suspected of causing genetic defects.
H373 - May cause damage to organs through prolonged or repeated exposure.
: P102 - Keep out of reach of children.
P405 - Store locked up.
P210 - Keep away from hot surfaces, open flames, sparks, heat. – No smoking.
P260 - Do not breathe vapours.
P280 - Wear face shield, protective gloves, protective clothing.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 - Do NOT induce vomiting.
P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

| Component | |
|--|---|
| 2-ethylhexan-1-ol (104-76-7) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |
| hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|---------|---|
| C8-C26 branched and linear hydrocarbons – Distillates | CAS-No.: 848301-67-7 EC-No.: 481-740-5 REACH-no: 01-0000020119-75 | 25 – 50 | Asp. Tox. 1, H304 EUH066 |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|--|---------|--|
| 2-ethylhexan-1-ol substance with a Community workplace exposure limit | CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289-20 | 10 – 25 | Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 |
| 2-butoxyethanol substance with a Community workplace exposure limit | CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108-36 | 10 – 25 | Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 |
| reaction mass of ethylbenzene and xylene | EC-No.: 905-588-0 REACH-no: 01-2119488216-32 | 10 – 25 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |
| polyetheramine | CAS-No.: 224622-34-8 | 5 – 10 | Skin Irrit. 2, H315 Aquatic Chronic 3, H412 |
| Di-tert-butyl peroxide | CAS-No.: 110-05-4 EC-No.: 203-733-6 EC Index-No.: 617-001-00-2 REACH-no: 01-2119513335-48 | 2,5 – 5 | Flam. Liq. 2, H225 Org. Perox. E, H242 Muta. 2, H341 Aquatic Chronic 3, H412 |
| hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | EC-No.: 919-164-8 REACH-no: 01-2119473977-17 | 1 – 2,5 | STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 EUH066 |

Specific concentration limits:

| Name | Product identifier | Specific concentration limits (%) |
|--|---|-----------------------------------|
| reaction mass of ethylbenzene and xylene | EC-No.: 905-588-0 REACH-no: 01-2119488216-32 | (10 ≤ C < 100) STOT RE 2, H373 |

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

First-aid measures after skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after ingestion : If swallowed, rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of causing genetic defects.
Symptoms/effects after inhalation : Harmful if inhaled.
Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking. Harmful in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : Abdominal pain. Headache. Risk of aspiration pneumonia. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. AFFF foam. ABC-powder.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Take precautionary measures against static discharges. The vapours are denser than air and may travel along the ground. Distance ignition possible.
Explosion hazard : No direct explosion hazard.

5.3. Advice for firefighters

Firefighting instructions : Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable gloves and eye/face protection. protective clothing.
Emergency procedures : Mark the danger area. Ventilate spillage area. Prevent flow to low areas. In confined space use self-contained breathing apparatus. Take off contaminated clothing.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Contain leaking substance, pump over in suitable containers.
Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Meet the legal requirements. Repeated exposure may cause skin dryness or cracking. Provide good ventilation in process area to prevent formation of vapour. Presents no particular risk when handled in accordance with good occupational hygiene practice.
- Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Wash with plenty of water/.... Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Take precautionary measures against static discharge. Does not require any specific or particular technical measures.
- Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Store in a well-ventilated place. Meet the legal requirements. Keep container tightly closed.
- Storage temperature : < 45 °C
- Storage area : Meet the legal requirements. Protect from heat and direct sunlight. Fireproof storeroom. Ventilation along the floor.
- Special rules on packaging : Keep only in original container. Labelling according to.

7.3. Specific end use(s)

Read label before use. Observe the label precautions. See product bulletin for detailed information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| 2-ethylhexan-1-ol (104-76-7) | |
|--|------------------------------------|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| IOEL TWA | 5,4 mg/m ³ |
| IOEL TWA [ppm] | 1 ppm |
| Germany - Occupational Exposure Limits (TRGS 900) | |
| AGW (OEL TWA) [1] | 110 mg/m ³ |
| AGW (OEL TWA) [2] | 20 ppm |
| 2-butoxyethanol (111-76-2) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | 2-Butoxyethanol |
| IOEL TWA | 98 mg/m ³ |
| IOEL TWA [ppm] | 20 ppm |
| IOEL STEL | 246 mg/m ³ |
| IOEL STEL [ppm] | 50 ppm |
| Remark | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| Belgium - Occupational Exposure Limits | |
| Local name | 2-Butoxyéthanol # 2-Butoxy-ethanol |
| OEL TWA | 98 mg/m ³ |
| OEL TWA [ppm] | 20 ppm |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| 2-butoxyethanol (111-76-2) | |
|--|--|
| OEL STEL | 246 mg/m ³ |
| OEL STEL [ppm] | 50 ppm |
| Regulatory reference | Koninklijk besluit/Arrêté royal 11/03/2002 |
| France - Occupational Exposure Limits | |
| VME (OEL TWA) | 49 mg/m ³ |
| VME (OEL TWA) [ppm] | 10 ppm |
| VLE (OEL C/STEL) | 246 mg/m ³ |
| VLE (OEL C/STEL) [ppm] | 50 ppm |
| Hungary - Occupational Exposure Limits | |
| AK (OEL TWA) | 98 mg/m ³ |
| CK (OEL STEL) | 246 mg/m ³ |
| Netherlands - Occupational Exposure Limits | |
| TGG-8u (OEL TWA) | 100 mg/m ³ |
| TGG-8u (OEL TWA) [ppm] | 20 ppm |
| TGG-15min (OEL STEL) | 246 mg/m ³ |
| TGG-15min (OEL STEL) [ppm] | 50 ppm |
| hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | |
| Belgium - Occupational Exposure Limits | |
| OEL TWA | 533 mg/m ³ |
| OEL TWA [ppm] | 100 ppm |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA [ppm] | 100 ppm |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

| C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7) | |
|---|-------------------------|
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 2,06 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 1,68 mg/kg dwt |
| PNEC (STP) | |
| PNEC sewage treatment plant | 10 mg/l |
| 2-ethylhexan-1-ol (104-76-7) | |
| DNEL/DMEL (Workers) | |
| Acute - local effects, inhalation | 53,2 mg/m ³ |
| Long-term - systemic effects, dermal | 23 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 12,8 mg/m ³ |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| 2-ethylhexan-1-ol (104-76-7) | |
|--|---------------------------|
| Long-term - local effects, inhalation | 53,2 mg/m³ |
| DNEL/DMEL (General population) | |
| Acute - local effects, inhalation | 26,6 mg/m³ |
| Long-term - systemic effects, oral | 1,1 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 2,3 mg/m³ |
| Long-term - systemic effects, dermal | 11,4 mg/kg bodyweight/day |
| Long-term - local effects, inhalation | 26,6 mg/m³ |
| PNEC (Water) | |
| PNEC aqua (freshwater) | 0,017 mg/l |
| PNEC aqua (marine water) | 0,0017 mg/l |
| PNEC aqua (intermittent, freshwater) | 0,17 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 0,284 mg/kg dwt |
| PNEC sediment (marine water) | 0,0284 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 0,047 mg/kg dwt |
| PNEC (STP) | |
| PNEC sewage treatment plant | 10 mg/l |
| 2-butoxyethanol (111-76-2) | |
| DNEL/DMEL (Workers) | |
| Acute - systemic effects, dermal | 89 mg/kg bodyweight/day |
| Acute - systemic effects, inhalation | 1091 mg/m³ |
| Long-term - systemic effects, dermal | 125 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 98 mg/m³ |
| Long-term - local effects, inhalation | 246 mg/m³ |
| DNEL/DMEL (General population) | |
| Acute - systemic effects, dermal | 89 mg/kg bodyweight |
| Acute - systemic effects, inhalation | 426 mg/m³ |
| Acute - systemic effects, oral | 26,7 mg/kg bodyweight |
| Long-term - systemic effects, oral | 6,3 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 59 mg/m³ |
| Long-term - systemic effects, dermal | 75 mg/kg bodyweight/day |
| Long-term - local effects, inhalation | 147 mg/m³ |
| PNEC (Water) | |
| PNEC aqua (freshwater) | 8,8 mg/l |
| PNEC aqua (marine water) | 0,88 mg/l |
| PNEC aqua (intermittent, freshwater) | 9,1 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 34,6 mg/kg dwt |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| | |
|---|---------------------------|
| 2-butoxyethanol (111-76-2) | |
| PNEC sediment (marine water) | 3,46 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 2,33 mg/kg dwt |
| PNEC (STP) | |
| PNEC sewage treatment plant | 463 mg/l |
| reaction mass of ethylbenzene and xylene | |
| DNEL/DMEL (Workers) | |
| Acute - systemic effects, inhalation | 442 mg/m ³ |
| Acute - local effects, inhalation | 442 mg/m ³ |
| Long-term - systemic effects, dermal | 212 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 221 mg/m ³ |
| Long-term - local effects, inhalation | 221 mg/m ³ |
| DNEL/DMEL (General population) | |
| Acute - systemic effects, inhalation | 260 mg/m ³ |
| Acute - local effects, inhalation | 260 mg/m ³ |
| Long-term - systemic effects, oral | 12,5 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 65,3 mg/m ³ |
| Long-term - systemic effects, dermal | 125 mg/kg bodyweight/day |
| Long-term - local effects, inhalation | 65,3 mg/m ³ |
| PNEC (Water) | |
| PNEC aqua (freshwater) | 0,327 mg/l |
| PNEC aqua (marine water) | 0,327 mg/l |
| PNEC aqua (intermittent, freshwater) | 0,327 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 12,46 mg/kg dwt |
| PNEC sediment (marine water) | 12,46 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 2,31 mg/kg dwt |
| Di-tert-butyl peroxide (110-05-4) | |
| DNEL/DMEL (Workers) | |
| Long-term - systemic effects, dermal | 3 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 20 mg/m ³ |
| PNEC (Water) | |
| PNEC aqua (freshwater) | 0,144 mg/l |
| PNEC aqua (marine water) | 0,014 mg/l |
| PNEC aqua (intermittent, freshwater) | 0,36 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 15 mg/kg dwt |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Di-tert-butyl peroxide (110-05-4) | |
|-----------------------------------|----------------|
| PNEC sediment (marine water) | 1,5 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 2,94 mg/kg dwt |
| PNEC (STP) | |
| PNEC sewage treatment plant | 10 mg/l |

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide good ventilation in process area to prevent formation of vapour. Does not require any specific or particular technical measures.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

No additional information available

8.2.2.2. Skin protection

Hand protection:

Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer

8.2.2.3. Respiratory protection

No additional information available

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|----------------------|--|
| Physical state | : Liquid |
| Colour | : Colourless. |
| Appearance | : clear. |
| Odour | : characteristic. |
| Odour threshold | : Not available |
| Melting point | : Not available |
| Freezing point | : Not available |
| Boiling point | : Not available |
| Flammability | : Not available |
| Oxidising properties | : Non oxidizing material according to EC criteria. |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| | |
|---|---|
| Lower explosion limit | : Not available |
| Upper explosion limit | : Not available |
| Flash point | : 39 °C (ASTM D93) |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| pH | : Not available |
| Viscosity, kinematic | : 2,5 mm ² /s @40°C |
| Solubility | : Not available |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Vapour pressure | : Not available |
| Vapour pressure at 50°C | : Not available |
| Density | : 820 kg/m ³ @ 20°C (ASTM D4052) |
| Relative density | : Not available |
| Relative vapour density at 20°C | : Not available |
| Particle characteristics | : Not applicable |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Additional information : The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

| | |
|-----------------------------|-----------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Harmful if inhaled. |

| Petrol Pre Emission Test Treatment | |
|------------------------------------|----------------|
| ATE CLP (vapours) | 19,075 mg/l/4h |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| | |
|---|--|
| C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7) | |
| LD50 oral rat | > 5000 mg/kg bodyweight Sprague-Dawley |
| LD50 dermal rat | > 2000 mg/kg bodyweight Sprague-Dawley |
| 2-ethylhexan-1-ol (104-76-7) | |
| LD50 oral rat | 2047 mg/kg |
| LD50 dermal rabbit | > 3000 mg/kg |
| LC50 Inhalation - Rat | 1,1 mg/l/4h |
| 2-butoxyethanol (111-76-2) | |
| LD50 oral rat | 1200 mg/kg bodyweight Rat |
| LD50 dermal rat | > 2000 mg/kg bodyweight Sprague-Dawley |
| reaction mass of ethylbenzene and xylene | |
| LD50 oral rat | 3523 mg/kg bodyweight F344/N |
| LD50 dermal rabbit | 12126 mg/kg bodyweight New Zealand White |
| Di-tert-butyl peroxide (110-05-4) | |
| LD50 oral rat | > 2000 mg/kg bodyweight Wistar |
| LD50 dermal rat | > 2000 mg/kg bodyweight Wistar |
| LC50 Inhalation - Rat | > 22 mg/l/4h Wistar |
| hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | |
| LD50 oral rat | > 15000 mg/kg |
| LD50 dermal rabbit | > 3400 mg/kg |
| LC50 Inhalation - Rat | > 13,1 mg/l/4h |
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Suspected of causing genetic defects. |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause respiratory irritation. |
| 2-ethylhexan-1-ol (104-76-7) | |
| STOT-single exposure | May cause respiratory irritation. |
| reaction mass of ethylbenzene and xylene | |
| STOT-single exposure | May cause respiratory irritation. |
| STOT-repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |
| reaction mass of ethylbenzene and xylene | |
| STOT-repeated exposure | May cause damage to organs (hearing organs) through prolonged or repeated exposure (oral, if inhaled). |
| hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | |
| STOT-repeated exposure | Causes damage to organs (central nervous system) through prolonged or repeated exposure. |
| Aspiration hazard | : May be fatal if swallowed and enters airways. |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Petrol Pre Emission Test Treatment | |
|--|-----------------|
| Viscosity, kinematic | 2,5 mm²/s @40°C |
| C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7) | |
| Viscosity, kinematic | 2 – 4,5 mm²/s |
| 2-butoxyethanol (111-76-2) | |
| Viscosity, kinematic | < 3,7 mm²/s |
| reaction mass of ethylbenzene and xylene | |
| Viscosity, kinematic | < 0,74 mm²/s |
| Aliphatic, alicyclic or aromatic hydrocarbon | Yes |
| polyetheramine (224622-34-8) | |
| Aliphatic, alicyclic or aromatic hydrocarbon | Yes |
| Di-tert-butyl peroxide (110-05-4) | |
| Viscosity, kinematic | < 1,1 mm²/s |
| hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | |
| Viscosity, kinematic | < 2,2 mm²/s |
| Aliphatic, alicyclic or aromatic hydrocarbon | Yes |

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|---|
| Ecology - general | : This product contains hazardous components for the aquatic environment. |
| Ecology - water | : Harmful to aquatic life with long lasting effects. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified |

| C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7) | |
|---|--|
| LC50 - Fish [1] | > 1000 mg/l @96h Pimephales promelas |
| EC50 - Crustacea [1] | > 1000 mg/l @48h Daphnia magna |
| EC50 - Other aquatic organisms [1] | > 1000 mg/l @72h Pseudokirchneriella subcapitata |
| NOEC (acute) | > 1000 mg/l @48h Daphnia magna |
| 2-ethylhexan-1-ol (104-76-7) | |
| LC50 - Fish [1] | 96h 28,2 mg/l pimephales promelas |
| EC50 - Crustacea [1] | 48h 39 mg/l daphnia magna |
| EC50 - Other aquatic organisms [1] | 72h 11,5 mg/l algae (desmodesmus subspicatus) |
| 2-butoxyethanol (111-76-2) | |
| LC50 - Fish [1] | 96h 1464 mg/l Oncorhynchus mykiss |
| EC50 - Crustacea [1] | 48h 1800 mg/l Daphnia magna |
| EC50 - Other aquatic organisms [1] | 72h 911 mg/l Pseudokirchneriella subcapitata |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| 2-butoxyethanol (111-76-2) | |
|--|--|
| NOEC (acute) | 72h 88 mg/l Pseudokirchneriella subcapitata |
| reaction mass of ethylbenzene and xylene | |
| LC50 - Fish [1] | > 2,6 mg/l @96h |
| EC50 - Other aquatic organisms [1] | 72h 2,2 mg/l |
| Di-tert-butyl peroxide (110-05-4) | |
| LC50 - Fish [1] | 96h 805,089 mg/l Pimephales promelas |
| EC50 - Crustacea [1] | > 73,1 mg/l @48h Daphnia magna |
| EC50 - Other aquatic organisms [1] | ≈ 15 mg/l @72h Pseudokirchneriella subcapitata |

12.2. Persistence and degradability

| C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7) | |
|---|------------------------|
| Persistence and degradability | Readily biodegradable. |
| 2-ethylhexan-1-ol (104-76-7) | |
| Persistence and degradability | Readily biodegradable. |
| 2-butoxyethanol (111-76-2) | |
| Persistence and degradability | Readily biodegradable. |

12.3. Bioaccumulative potential

| C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7) | |
|---|---------------------------|
| Partition coefficient n-octanol/water (Log Pow) | > 6,5 @40°C |
| 2-ethylhexan-1-ol (104-76-7) | |
| Bioaccumulative potential | No bioaccumulation. |
| 2-butoxyethanol (111-76-2) | |
| Bioaccumulative potential | Slightly bioaccumulative. |
| Di-tert-butyl peroxide (110-05-4) | |
| Partition coefficient n-octanol/water (Log Pow) | 3,2 @22°C |

12.4. Mobility in soil

| 2-butoxyethanol (111-76-2) | |
|----------------------------|-------------------|
| Ecology - soil | Small adsorption. |

12.5. Results of PBT and vPvB assessment

| Component | |
|--|---|
| 2-ethylhexan-1-ol (104-76-7) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |
| hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |

12.6. Endocrine disrupting properties

No additional information available

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations



13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.

European List of Waste (LoW) code : 18 01 06* - chemicals consisting of or containing dangerous substances
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

| ADR | IMDG | IATA | ADN | RID |
|---|--|---|---|---|
| 14.1. UN number or ID number | | | | |
| UN 1993 | UN 1993 | UN 1993 | UN 1993 | UN 1993 |
| 14.2. UN proper shipping name | | | | |
| FLAMMABLE LIQUID, N.O.S. (xylenes, di-tert- butylperoxide) | (xylenes, di-tert- butylperoxide) | (xylenes, di-tert- butylperoxide) | (xylenes, di-tert- butylperoxide) | (xylenes, di-tert- butylperoxide) |
| Transport document description | | | | |
| UN 1993 FLAMMABLE LIQUID, N.O.S. (xylenes, di-tert-butylperoxide), 3, III, (D/E) | UN 1993 (xylenes, di-tert- butylperoxide), 3 | UN 1993 (xylenes, di-tert- butylperoxide), 3 | UN 1993 (xylenes, di-tert- butylperoxide), 3 | UN 1993 (xylenes, di-tert- butylperoxide), 3 |
| 14.3. Transport hazard class(es) | | | | |
| 3 | 3 | 3 | 3 | 3 |
|  | Not applicable | Not applicable | Not applicable |  |
| 14.4. Packing group | | | | |
| III | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment: No | Dangerous for the environment: No Marine pollutant: No | Dangerous for the environment: No | Dangerous for the environment: No | Dangerous for the environment: No |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 274, 601, 640E
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Hazard identification number (Kemler No.) : 30

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Orange plates

:



Tunnel restriction code (ADR)

: D/E

EAC code

: •3YE

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

France

| Occupational diseases | |
|-----------------------|---|
| Code | Description |
| RG 84 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class II-1
Store unit : 5 liter
Classification remarks : R10 <H226;H304;H315;H319;H332;H335;H341;H373>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

| | |
|-------------------------------------|---|
| Acute Tox. 3 (Inhalation) | Acute toxicity (inhal.), Category 3 |
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment – Chronic Hazard, Category 3 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |

Petrol Pre Emission Test Treatment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| H242 | Heating may cause a fire. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H341 | Suspected of causing genetic defects. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects. |
| Muta. 2 | Germ cell mutagenicity, Category 2 |
| Org. Perox. E | Organic Peroxides, Type E |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT RE 1 | Specific target organ toxicity – Repeated exposure, Category 1 |
| STOT RE 2 | Specific target organ toxicity – Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation |

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.